



08-10-00

A

THE COMMISSIONER OF PATENTS AND TRADEMARKS
Washington D.C. 20231
Box Patent Applications

Case Docket No. FUJH 17.615
Filed by Express Mail
(Receipt No. EL522338425US)
on August 9, 2000
pursuant to 37 CFR 1.10
by Lydia Gonzalez



S I R:

Transmitted herewith for filing is: ☒ a new application
☐ a c-i-p application of S.N. _____ filed _____

Inventor(s): Naoki AIHARA; Hichiro HAYAMI; Iwao TADA; Tomoyuki YAMAGUCHI

For **ATM SWITCHING SYSTEM AND METHOD FOR SWITCHOVER BETWEEN
WORKING CHANNEL AND PROTECTION CHANNEL IN AN ATM NETWORK**

Enclosed are:

- ☒ 4 sheets of drawings.(Figs. 1-7)
- ☒ Specification, including claims and abstract (16 pages)
- ☒ Declaration
- ☒ An assignment of the Invention to FUJITSU LIMITED
- ☒ A certified copy of Japanese Application No(s). 11-224903
- ☒ An associate power of attorney
- ☐ A verified statement to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27
- ☒ Post card
- ☒ Recording fee (as indicated below)
- ☒ Information Disclosure Statement, PTO-1449, copies of 1 references
- ☐ Other _____
- ☐ Other _____

	Col. 1	Col. 2
FOR:	NO. FILED	NO. EXTRA
BASIC FEE		
TOTAL CLAIMS	8-20 =	0
INDEP CLAIMS	3-3 =	0
<input type="checkbox"/> MULTIPLE DEPENDENT CLAIMS PRESENTED		

*If the difference in Col. 1 is less than
zero, enter "0" in Col. 2

SMALL ENTITY	
RATE	FEE
	\$345
x 9 =	\$
x 39 =	\$
x 130 =	\$
TOTAL	\$

OTHER THAN A SMALL ENTITY	
RATE	FEE
	\$690
x 18 =	\$
x 78 =	\$
x 260 =	\$
TOTAL	\$690

☐ Please charge our Deposit Account No. 08-1634 the amount of _____ to cover the filing fee
and recording fee (if any)

☒ A check in the amount of \$730.00 to cover the filing fee and the recording fee (if any) is enclosed.

☒ The Commissioner is hereby authorized to charge payment of any fee associated with this communication or
credit overpayment to Deposit Account No. 08-1634. A duplicate coy of this sheet is enclosed.

Helfgott & Karas, P.C.
60th Floor
Empire State Building
New York, New York 10118-6098
(212)643-5000

Respectfully Submitted,

Date:8/09/00

Any fee due with this paper, not fully
covered by an enclosed check, may be
charged on Deposit Acct No. 08-1634

- ☐ Aaron B. Karas, Reg. No. 18,923
- ☒ Samson Helfgott, Reg. No. 23,072
- ☐ Leonard Cooper, Reg. No. 27, 625
- ☐ Linda S. Chan, Reg. No. 42,400
- ☐ Jacqueline M. Steady, Reg. No. 44,354
- ☐ Harris A. Wolin, Reg. No. 39,432

path establishment and switchover.

SUMMARY OF THE INVENTION

5 It is therefore an object of the present invention to provide a method and equipment for switchover between a working channel and a protection channel in an ATM network, with a simplified and efficient manner to compensate the aforementioned disadvantage of the physical layer APS.

10 A method and equipment for addressing the above issue of the present invention to switch over between a working channel and a protection channel in an ATM network includes the following steps: indicating in a cell for transmission whether the cell is object for channel switchover; duplicating the cell in each connection; transmitting the duplicated cell simultaneously
15 both to a working channel and to a protection channel; and selecting a received cell according to an indication whether the cell belongs to a connection currently in working state.

Preferably, a cell not indicated as being in a connection currently in working state is discarded.

20 Furthermore, preferably, the indication of cell of which connection is not object for the switchover is specified at the unit of a connection group.

Other features of the present invention will be apparent by the following description on the embodiments of the invention
25 referring to the accompanied drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a basic concept of the physical layer APS applied in the present invention.

FIG. 2 shows a configuration diagram of a node C and a node F located at either ends of a protection domain shown in FIG.

5 1.

FIG. 3 shows a configuration block diagram realizing a functional element of a demultiplexer (DMX) 3-2.

FIG. 4 shows a configuration block diagram of line interface portions 2'-1 to 2'-n in the downstream side of node C shown in FIG. 2.

FIG. 5 shows a configuration block diagram of line interface portions 2-1 to 2-n in the upstream side of node F shown in FIG. 2.

FIG. 6 shows an embodiment for setting an ACT bit into an ACT bit set table 25 promptly to reduce an APS switchover time.

FIG. 7 shows a configuration block diagram of a multiplexer (MUX) 3-1 shown in FIG. 2.

PREFERRED EMBODIMENTS OF THE INVENTION

20 An embodiment of the present invention is described hereinafter with the accompanied drawings wherein like numerals and symbols refer to like parts.

Prior to explaining the embodiments of the present invention, a basic concept of the 'physical layer APS' is explained first for easier understanding of the invention.

25 In FIG. 1, a general diagram of the physical layer APS is shown. A node terminating the ATM layer is shown indicating a

situation that a connection is currently established between a node A to a node B. ATM cells each consisting of a header and a payload are transmitted on the connection.

As routes of the connection, a path is being established
5 through nodes C -D -E -F constituting a working channel, and also a path through nodes C -G -H -F constituting a protection channel. The duplicated channel segment consisting of the working channel and the protection channel is called a 'protected domain', to which the physical layer APS is applied.

10 Note that a transmission path shown in FIG. 1 does not mean a physical line, but the path means a virtual channel on the ATM layer.

In such a network configuration, the physical layer APS is a mechanism to switch over from a working channel to a protection
15 channel in case a failure occurs at an arbitrary point on the working channel. The switchover is generally triggered by the detection of an alarm indicating signal on a virtual path and a virtual channel (VP/VC-AIS; hereafter simply referred to as AIS). The above AIS is detected at a terminating point (node
20 F in the case of FIG. 1) of a segment which is defined as a protected domain of the connection.

For example, when a physical failure such as a breakdown of a fiber transmission line occurs between node C and node D, this situation is detected at node D, producing an AIS cell to
25 forward from node D in the downstream direction (i.e. in the direction toward node F).

Here, the AIS cell is a cell containing an AIS in an ATM

cell header. The AIS cell is detected by node F at which the protected domain is terminated. On this detection, the relevant segment is declared inoperable. At the same time an APS procedure is started.

5 The APS can be classified into the following schemes with respect to the provision of protection channels. One method is that one protection channel is provided corresponding to each working channel i.e. 1+1 or 1:1 scheme; the other is, using a shared protection channel, either one protection channel shared
10 by n working channels i.e. 1:n scheme, or m protection channels shared by n working channels i.e. m:n scheme ($m \leq n$).

 The difference between 1+1 scheme and 1:1 scheme is that in 1+1 scheme the identical cells are normally transmitted on both a working channel and a protection channel, while in 1:1
15 scheme cells are transmitted only on a channel currently in working state (i.e. a working channel).

 From another aspect, the APS can be classified into a VP/VC-APS method in which a switchover is carried out at the unit of each VP/VC (virtual path and virtual channel) connection,
20 and a VPG/VCG-APS method in which a switchover is carried out at the unit of a group of VP/VC connections.

 The object of the present invention is to realize the above-mentioned physical layer APS with a simplified configuration.

 In FIG. 2, there is shown a configuration example of a node
25 in accordance with the present invention. The node is located at either end of a protection domain shown in FIG. 1. Only node C and node F are shown in this figure where other intermediate

nodes are omitted.

Each node consists of an ATM switching system which is provided with the following elements: an ATM switch circuit (SW) 1 for performing cell switching function; line interface portions (LINF) 2'-1 to 2'-n for inserting cells, located at the external line side; and line interface portions (LINF) 2-1 to 2-n for extracting cells, located at the internal line side.

Also, there are provided in each node a multiplexer (MUX) 3-1 for multiplexing cells input from line interface portions 2-1 to 2-n, interfacing ATM switch circuit 1; a demultiplexer (DMX) 3-2 for demultiplexing multiplexed ATM cells, also interfacing ATM switch circuit 1; and a controller 4 for performing overall control function.

Referring to FIG. 2, an operation of the physical layer APS in accordance with the present invention is explained hereafter, where 1+1 or 1:1 scheme is taken as an example.

(1) At an initial state, the identical cells are being transmitted on both working channels and protection channels. In node C, a connection for the APS is identified at demultiplexer (DMX) 3-2 under the control of controller 4, to duplicate cells on a working channel side to a protection channel side.

(2) When a failure occurs on a working channel between node C and node D, node D detects the failure and then transmits an AIS cell in the downstream direction toward node F. This AIS cell is detected by node F, of which information is transferred to controller 4.

335030" 2864E950

(3) Controller 4 orders to switch over the connection (ACT) for the APS. Specifically, controller 4 orders ATM switch circuit 1 to switch over from line interface portion (LINF) 2-1 where the working channel is terminated to line interface portion (LINF) 2-i where the protection channel is terminated. More specifically, using a function provided in each line interface portion (LINF) 2-1 to 2-n, an ACT bit in each ATM cell header in transmission is set either 'ON' (which denotes line interface portion 2-i i.e. the protection channel side is in working state), or 'OFF' (which denotes line interface portion 2-1 i.e. the working channel side is in working state).

(4) A mechanism is provided in multiplexer (MUX) 3-1 that the ACT bit in each cell received from line interface portions 2-1 to 2-n is examined to determine whether the cell is to be transmitted. Only cells having proper ACT indication are allowed to transmit. In multiplexer (MUX) 3-1 in node F, a previous condition that only ATM cells received on the working channel are transmitted through and ATM cells on the protection channel are rejected to transmit, is now switched over to that only ATM cells received on the protection channel can be transmitted through. Thus an operation of the physical layer APS is completed.

According to the present invention, the following functional elements are provided for realizing a sequence of operation described above in an ATM node;

(1) in demultiplexer (DMX) 3-2, duplicating cells on a working channel to a protection channel side at the unit of

either a connection or a connection group,

(2) in line interface portions 2-1 to 2-n, providing each ATM cell header with an ACT bit for specifying ACT (in working condition) at the unit of either a connection or a connection group, and

(3) in multiplexer (MUX) 3-1, transmitting only cells of which ACT is specified in each cell header.

A detailed embodiment of the functional elements (1) to (3) above is described hereinafter.

In FIG. 3, a functional element of demultiplexer (DMX) 3-2 provided in each node is shown.

In this FIG. 3, Tag-B is a tag provided in an ATM cell header for identifying an output channel. O-ICID-A is also provided in the ATM cell header, which is an 'internal channel identifier' for identifying a channel in an output channel indicated by Tag-B.

An APS identifier is also provided in the ATM cell header which enables to determine whether a connection (or a connection group) of the relevant cell is object for the APS processing or not.

The tag and the internal channel identifier explained above are set into an ATM cell header at either line interface portions 2-1 to 2-n and 2'-1 to 2'-n, multiplexer (MUX) 3-1, or ATM switch circuit 1, under the control of controller 4.

For example, in node C shown in FIG. 3, an APS identifier in an ATM cell input to demultiplexer (DMX) 3-2 is examined. If this APS identifier indicates the cell is object for the APS

(i.e. APS is 'ON'), then a cell duplication table 30 is referred to, using Tag-B and O-ICID-A as the reference keys.

Through the above procedure, information on an output line Tag-B(P) to be used for an protection channel and a channel
5 O-ICID-A(P) in the above output line is obtained. Then the ATM cell is duplicated and the information on an output line and a channel in the duplicated cell are respectively replaced by Tag-B(P) and O-ICID-A(P), to output to a cell buffer (FIFO) 31.

In FIG. 4, there is illustrated a configuration block
10 diagram of line interface portion 2-i on the internal line side which is provided in node D, for example, located in the downstream direction against node C. In this FIG. 4, O-VPI/VCI is stored in a cell header, showing a value of VPI/VCI (virtual path and virtual channel identifier) of an output line related
15 to the cell.

Using as a reference key an internal line and channel identifier O-ICID-A in an input ATM cell, a VPI/VCI conversion table 21 is referred to. Then, VPI/VCI to be forwarded to an external line is obtained from VPI/VCI conversion table 21.

20 The obtained VPI/VCI is set into the ATM cell header in a header modification portion 22, to forward to the external transmission line.

Also, in line interface portion 2-i on the internal line side, there is provided an alarm cell insertion circuit 20 to
25 insert an alarm cell named VP/VC-AIS. When a failure occurs between node C and node D, and node D detects this failure, an alarm cell is inserted according to a control command issued

from controller 4.

Here, an alarm cell is a kind of ATM cell in which an alarm indicating signal (AIS) is set in an ATM cell header. The alarm cell is detected in the downstream node (for example, node F in the network configuration shown in Fig. 1) to trigger THE APS operation.

In FIG. 5, there is shown a block diagram of a configuration example related to the input side of line interface portion 2-1 in node F which constitutes a terminal node of a protected domain. By referring to an ICID conversion table 23 using VPI/VCI, which is an external virtual path and virtual channel identifier stored in a header of an input ATM cell, as a reference key, a corresponding internal virtual path and virtual channel identifier, I-ICID-A, is obtained.

The reason of the above processing is that VPI/VCI composed of 22 bits requires large amount of circuits to process in ATM switch circuit 1. Therefore, VPI/VCI is converted into I-ICID-A which is a condensed form of the internal path and channel identifier. A header modification portion 24 replaces with the obtained I-ICID-A in an ATM cell header which.

Then, using the obtained I-ICID-A as a reference key, an APS identifier set table 25 is referred to. Depending on 'ON' or 'OFF' of an APS bit in APS identifier set table 25, whether the corresponding internal path and channel is object for the APS or not is determined.

Furthermore, using the value of I-ICID-A as a reference key, an ACT bit set table 26 is referred to. The ACT bit indicates

whether each object cell for the APS is actually to be transmitted to a destination terminal.

The APS bit and the ACT bit which have been referred to are attached to an ATM cell header by a header modification portion
5 27.

Values in those tables for determining that a cell is object for the APS etc. are set by an order from controller 4 either in advance or in case necessary.

Furthermore, in FIG. 5, an alarm cell extraction portion
10 28 is provided for extracting an alarm cell sent from an upstream node to inform to controller 4.

In FIG. 6, there is shown an embodiment for setting APS identifier set table 25 and ACT bit set table 26 by an order from controller 4 which is carried out in a procedure after the
15 APS is started. The embodiment intends to shorten the required time for an APS switchover by setting ACT bit set table 25 with high-speed.

In FIG. 5, when an APS switchover occurs, it is necessary to rewrite all data related to the corresponding connection in
20 ACT bit set table 25, which may necessitate large processing time.

On the other hand, according to the configuration shown in FIG. 6, a table 25 is provided for use of setting ACT bits at the unit of an APS group (APS-Gr.). This enables to set the table
25 from controller 4 at the unit of APS group i.e. in a batch of lines, instead of individual line by line, with less processing time.

In order to refer to this table 25, information is required to identify which APS group each connection belongs to. For this purpose, an APS group conversion table 29 is provided for obtaining APS-Gr from I-ICID-A having been extracted from ICID
5 conversion table 23. Each APS group is generally assigned corresponding to each outgoing line of ATM switch circuit 1.

Using an APS group obtained from APS group conversion table 29, an APS identifier set table 26 is referred to. Also ACT bit set table 25 is referred to using an APS group obtained from
10 APS group conversion table 29.

In FIG. 7, there is shown a configuration block diagram of multiplexer (MUX) 3-1 shown in FIG. 2. Among ATM cells received from each channel route SHW0 to SHWn, only ATM cells received on a protection channel side having 'ON' in each ACT bit are
15 transmitted through cell invalidation circuits 32-1 to 32-n. ATM cells transmitted through are then multiplexed by a multiplexing circuit 33 to forward to ATM switch circuit 1.

Having been explained referring to the accompanied drawings, the present invention provides a concrete configuration for realizing ATM layer protection switching (APS). An ATM switching
20 system according to the present invention can be provided with simple configuration.

The foregoing description of the embodiment is not intended to limit the invention to the particular examples. Any suitable
25 modification may be resorted to the scope of the invention. All features and advantages of the invention which fall within the scope of the invention are covered by the appended claims.

What is claimed is:

1. A method for switching over between a working channel
and a protection channel in an ATM network comprising the steps
5 of:

indicating in a cell for transmission whether a connection
of said cell is object for a switchover;

duplicating said cell at the unit of a connection;

transmitting the duplicated cells simultaneously to a
10 working channel and a protection channel;

indicating whether each cell belongs to a connection
currently in a working state; and

selecting a received cell which is included in the
connection in a working state.

15

2. A method for switching over between a working channel
and a protection channel according to claim 1, wherein a cell
having an indication of a connection currently not in a working
state is discarded.

20

3. A method for switching over between a working channel
and a protection channel according to claim 1, wherein an
indication whether said cell for transmission is included in
a connection object for a channel switchover is provided in said
25 cell at the unit of a connection group.

4. ATM switching equipment having a switchover function

between a working channel and a protection channel, said ATM switching equipment comprising:

5 a demultiplexer having functions of indicating in a cell for transmission whether said cell is object for a switchover, duplicating said cell at the unit of a connection, and transmitting the duplicated cells simultaneously to a working channel and a protection channel; and

10 a line interface means for selecting a received cell according to the indication whether said cell is included in a connection currently in a working state.

15 5. ATM switching equipment according to claim 4, wherein said cell having an indication of a connection currently not in a working state is discarded.

20 6. ATM switching equipment according to claim 4, wherein an indication whether said cell for transmission is included in a connection object for a switchover is provided in said cell at the unit of a connection group.

7. ATM switching equipment provided in an ATM network node comprising:

25 a means for duplicating a cell at the unit of a connection; a means for transmitting the duplicated cells simultaneously to a working channel and a protection channel; and

a table for indicating, at the unit of either a connection

or a connection group, whether a received cell is included in a connection currently in a working state using an ACT bit provided in a cell header,
enabling to select a received cell referred to by said table
5 according to the indication whether said received cell is included in a connection currently in a working state.

8. ATM switching equipment according to claim 7 further comprising:
10 a means for invalidating a received cell referred to by said table in the case said cell has an indication of being included in a connection currently not in a working state.

ABSTRACT

A method and ATM switching equipment are provided for switching over between a working channel and a protection channel in an ATM network. The physical layer APS (automatic protection switching) is basically adopted with a simplified means. The method includes the following process: An indication is provided in each cell for transmission whether the cell belongs to a connection currently in a working state via a working channel. Cells are duplicated on each connection basis. The duplicated cells are transmitted simultaneously onto both a working channel and a protection channel. Valid cells are selected from received cells according to the indication in each cell whether the relevant connection is currently in a working state.

FIG. 1





FIG. 2



SW:ATM Switch
DMX:Demultiplexer
MUX:Multiplexer
LINF:Line Interface

FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

AIR SWITCHING SYSTEM AND METHOD FOR SWITCHOVERBETWEEN WORKING CHANNEL AND PROTECTION CHANNELIN AN AIR NETWORK

上記発明の明細書（下記の欄でxが1がついていない場合は、本表に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、
（該当する場合） _____ に訂正されました。☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されたとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

006080 / 8E4E350

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)

外国での先行出願

11-224903

JAPAN

(Number)
(番号)

(Country)
(国名)

(Number)
(番号)

(Country)
(国名)

私は、第35編米国法典119条(e)項に基づいて下記の米国外の特許出願規定に記載された権利をここに主張いたします。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国外の特許出願に記載された権利、又は米国外を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国外の特許出願に開示されていない限り、その先行米国外出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

09/08/1999

(Day/Month/Year Filed)
(出願年月日)

☐

(Day/Month/Year Filed)
(出願年月日)

☐

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)
(出願番号)

(Filing Date)
(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁護士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

書類送付先

Aaron B. KARAS, Reg. No. 18,923; Samson HELFGOTT,
Reg. No. 23,072 and Leonard COOPER Reg. No. 27,625
Send Correspondence to:
HELGOTT & KARAS, P.C.
Empire State Building, 60th Floor
New York, New York 10118
United States of America

直接電話連絡先: (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

Helgott & Karas, P.C.
(212) 643-5000

唯一または第一発明者名	Full name of sole or first inventor
	Naoki AIHARA
発明者の署名	Inventor's signature
日付	Date
	Naoki Aihara 25/07/2000
住所	Residence
	Kawasaki, Japan
国籍	Citizenship
	Japan
私書箱	Post Office Address
	c/o FUJITSU LIMITED, 1-1, Kamikodanaka
	4-chome, Nakahara-ku, Kawasaki,
	211-8588 Japan
第二共同発明者	Full name of second joint inventor, if any
	Hichiro HAYAMI
第二共同発明者	Second inventor's signature
日付	Date
	Hichiro Hayami 25/07/2000
住所	Residence
	Kawasaki, Japan
国籍	Citizenship
	Japan
私書箱	Post Office Address
	c/o FUJITSU LIMITED, 1-1, Kamikodanaka
	4-chome, Nakahara-ku, Kawasaki,
	211-8588 Japan

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)

第三共同発明者	Full name of third joint inventor, if any Iwao TADA		
第三共同発明者	日付	Third inventor's signature Iwao Tada	Date 25/07/2000
住 所	Residence Kawasaki, Japan		
国 籍	Citizenship Japan		
私書箱	Post Office Address c/o FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki, 211-8588 Japan		
第四共同発明者	Full name of fourth joint inventor, if any Tomoyuki YAMAGUCHI		
第四共同発明者	日付	Fourth inventor's signature Tomoyuki Yamaguchi	Date 25/07/2000
住 所	Residence Kawasaki, Japan		
国 籍	Citizenship Japan		
私書箱	Post Office Address c/o FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki, 211-8588 Japan		

第五共同発明者	Full name of fifth joint inventor, if any		
第五共同発明者	日付	Fifth inventor's signature	Date
住 所	Residence		
国 籍	Citizenship		
私書箱	Post Office Address		
第六共同発明者	Full name of sixth joint inventor, if any		
第六共同発明者	日付	Sixth inventor's signature	Date
住 所	Residence		
国 籍	Citizenship		
私書箱	Post Office Address		

(第七以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for seventh and subsequent joint inventors.)

THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of: **Naoki AIHARA et al.**

Filed : **Concurrently herewith**

For : **ATM SWITCHING SYSTEM AND METHOD FOR
SWITCHOVER BETWEEN WORKING CHANNEL
AND PROTECTION CHANNEL IN AN ATM
NETWORK**

Serial No. : **Concurrently herewith**

August 9, 2000


Assistant Commissioner of Patents
Washington, D.C. 20231

SUB-POWER OF ATTORNEY

S I R:

I, Samson Helfgott, Reg. No. 23,072 attorney of record herein,
do hereby grant a sub-power of attorney to Linda S. Chan, Reg. No.
42,400, Jacqueline M. Steady, Reg. No., 44,354 and Harris A. Wolin,
Reg. No. 39,432 to act and sign in my behalf in the above-referenced
application.

Respectfully submitted,



Samson Helfgott
Reg.No 23,072

HELFGOTT & KARAS, P.C.
60th FLOOR
EMPIRE STATE BUILDING
NEW YORK, NY 10118
DOCKET NO.:FUJH17.615
LHH:power

Filed Via Express Mail
Rec. No.:EL522338425US
On: August 9, 2000
By: Lydia Gonzalez

Any fee due as a result of this paper,
not covered by an enclosed check may
be charged on Deposit Acct. No. 08-
1634.

006080 " 4244E960